

PDLC Power controller

Product catalog



Ghost Tint Transformer lv 1



Product Parameter

Input	100-120VAC 60Hz / 200-240VAC 50Hz		
Output	Regular 60VAC; The output frequency follows the input frequency; Customizable output 36-110VAC.		
Power	Can be chosen 30W / 50W.		
Protection	Overcurrent protection, overvoltage protection, short circuit protection, front stage safety capacitors fuse.		
Function	Remote receiver,wire control port.		
Size	120*99*65mm		
Weight (30W)	0.95kg	Weight (50W)	1.1kg

Ghost Tint Transformer



Product Parameter

Input	100-120VAC 60HZ / 200-240VAC 50HZ
Output	Regular 60VAC; The output frequency follows the input frequency; Customizable output 36-110VAC.
Power	100W
Protection	Overcurrent protection, overvoltage protection, short circuit protection, front stage safety capacitors fuse.
Function	Remote receiver, wire control port.
Size	180*109*76mm
Weight	2.26kg

Ghost Tint Transformer lv



Product Parameter

Input	100-120VAC 60Hz / 200-240VAC 50Hz		
Output	Regular 60VAC; The output frequency follows the input frequency; Customizable output 36-110VAC.		
Power	Can be chosen 200W / 300W/ 500W.		
Protection	Overcurrent protection, overvoltage protection, short circuit protection,front stage safety capacitors fuse.		
Function	Remote receiver,wire control port.		
Size	200*120*100mm		
Weight (200W)	3.5kg	Weight (300W)	4.2kg
		Weight (500W)	5kg